



PRODUCT DATASHEET

AerSMASH TYPE: AS2000



**AerSMASH for clean indoor air
and quality retention of your products**

AerSMASH pure improvement.

AerSMASH Type AS2000

Type AS2000 is suitable for the elimination of bacteria, fungi and odors for rooms with a capacity of 2300 m³ per hour. The units are standard equipped with safety valves, pre-filtering, pre-programmed control, plasma cartridges with integrated electrostatic discharge (ESD) and motor.

Housing The boxes are made of high-quality SS 316 material. Including 4x lifting eye

Capacity 2300 M³

Weight 150 - 200 kgs

Plug & Play 220-240 V, 50-60 Hz, through 4-pole plug, cable length 1.5 meter , max 3,8A

Quarantee 24 months after installation or 36 months after delivery, with the exception of cartridges and pre-filters, which must be replaced according to use.

NFC Units are equipped with a Near Field Communication (NFC) for wireless setting. This is set ex works in accordance with the application at the customer.

Dimensions in mm

L	B	H
2850	680	720



Technical data

Sealing	EPDM	
Motor	DA-9/7 CM/AL; 373 Watt	
Cartridge	12V, plastic (ABS), 24 Watt per unit	
Pre filter	High Efficiency Particulate Air (hepa)	
CE	Ja	Declaration of conformity
Certifications	NEN-EN-IEC 60335-1:2012 EN60335-2-65:2003 +A1:2008+ NEN-EN-IEC C1: 2004+A11:2012 EN50366:2003 +A1:2006 or EN 62233:2008 NEN-EN-IEC 60730-1:2011 EN 60335 DIN EN 60335-2-65:2003 EMC (2004/108/EC): EMC (2006/95/EC) Protection Class III Appliance	