

A healthy working environment

PRODUCT DATASHEET


AerSMASH TYPE: AS2AR



Minimum of 90% decrease in aerosols



95% decrease of penicillium levels



Up to a 97% decrease of harmful pollutants



Why companies choose AerSMASH

- ✓ The best air quality
- ✓ No blind spots
- ✓ Plug and play installation
- ✓ Save energy
- ✓ For every space

Healthy Buildings

Eliminate odors, pollen, bacteria, viruses, fungi, smoke and other harmful substances from the air for a healthy working and living environment

AerSMASH Type AS2AR

Type AS2AR is suitable for reducing aerosols, odors, bacteria and fungi in rooms with a volume of +/-500 m³. The units are standard equipped with pre-filtering, programmed control, plasma cartridges with integrated electrostatic discharge (ESD) and a motor.

Housing The housing is manufactured from steel
 Coating is applied as standard with colour RAL 9010 (off white)
 Other colours available on request

Capacity Suitable for spaces up to 500 M³

Weight 15 kgs

Plug & Play 220-240 V, 50-60 Hz, through 2-pole plug, cable length 4 meter

Guarantee 24 months after installation or 36 months after delivery, with the exception of cartridges and pre-filters, which must be replaced according to use.

NFC Units are equipped with a Near Field Communication (NFC) for wireless setting. This is set ex works in accordance with the application at the customer.

Dimensions in mm

D	W	H
260	500	700



Technical data

Sealing	EPDM	
Motor	EBM Papst DC; max 39Db, 200 Watt	
Cartridge	12V, plastic (ABS), 24 Watt 2x	
Pre filter	High Efficiency Particulate Air (hepa)	
CE	Yes	Declaration of conformity
Certifications	NEN-EN-IEC 60335-1:2012 EN60335-2-65:2003 +A1:2008+ NEN-EN-IEC C1: 2004+A11:2012 EN50366:2003 +A1:2006 or EN 62233:2008 NEN-EN-IEC 60730-1:2011 EN 60335 DIN EN 60335-2-65:2003 EMC (2004/108/EC): EMC (2006/95/EC) Protection Class III Appliance	